



Promalene PP120PW

*Polypropylene Homopolymer
Powder*

**Melt Index –12 gr / 10 min
Density; 0.900 gr / cc**

Suggested Applications

*Master Batch
Compounds*

Nominal Properties

PROPERTY	TEST METHOD	Unit	Value
<i>Melt Index 230°C/ 2.16 kg</i>	<i>D1238</i>	<i>g/10 min.</i>	<i>12</i>
<i>Tensile yield strength</i>	<i>D 638</i>	<i>PSI</i>	<i>5,100</i>
<i>Elongation @yield</i>	<i>D 638</i>	<i>%</i>	<i>10</i>
<i>Elongation @break</i>	<i>D 638</i>	<i>%</i>	<i>200</i>
<i>Flexural Modulus</i>	<i>D 790A</i>	<i>PSI</i>	<i>220,000</i>
<i>Heat Deflection Temperature</i>	<i>D 648</i>	<i>C(F)</i>	<i>104(220)</i>

This material meets the requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520

Makes no representation or warranty of any kind, express or implied, with respect to this product, as to merchantability, Fitness for particular purpose or otherwise. The data listed represents average values and are believed to be reliable, They are given for information; no guarantee of their accuracy is made, however, and the product is sold upon condition that purchasers shall make their own test to determinate the characteristics of the product and the suitability of the product for their particular process.